



# HT580

## Intelligent Ultra-Compact Terminal



### Cutting-Edge Design

The Unitech HT580 presents a new cutting-edge design that changes the way you think of portable terminals. The HT580 provides a simple and user-friendly interface that gives you full control over a wide range of data capabilities.

### One-Hand Operation

The HT580's compact design is perfect for one-hand operation. It's a versatile tool that enhances your work effectiveness and efficiency. The HT580's keypad is designed with a cell phone-style touch and feel that everyone is familiar with. The large alphanumeric keys are easily identifiable with bright and bold graphics. The HT580 is a great match for retail markets or other small businesses that need simple, straightforward data entry and bar code scanning.

### Easily Programmable

EasyJob application generator (included) is an easy-to-use programming tool for fast HT580 setup.

### Features

- Compact and lightweight design
- Integrated CCD bar code scanner
- Built-in Bluetooth (optional)
- IP42 Rated
- User-friendly 18-key keypad
- All-in-one package
- Dimensions: 123mm x 55mm x 25mm
- Weight: 150 grams

### System

CPU	STUPSD3354DV
OS	Proprietary in C Language
Memory	Flash ROM: 512KB
Keypad	18 keys, including 1 scan trigger
Display	128 x 64 pixels
Real Time Clock	System date and time

### Power Management

Main Battery	One rechargeable Li-Ion battery pack @ 3.7V, 730mAh
Battery Charging	From fully discharged to fully charged in about 8 hours via cradle or cable
Operation Time	Up to 8 hours

### Scanner and Symbologies

Scanner	CCD Scan Engine	
Skew Angle	±25° @ 15.6 mil (0.39mm)	
Pitch Angle	±55° @ 15.6 mil (0.39mm)	
Rotation Angle	±25° @ 15.6 mil (0.39mm)	
Reading Distance	5mil - Code39	60mm ~ 100mm
Depth of Field (PCS = 90%)	6mil - Code39	60mm ~ 130mm
	15.6mil - Code 39	60mm ~ 190mm
Symbologies	China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, IATA 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, Telepen, UK Plessey Code, UPC/EAN	

### Communication

Bluetooth	Compliant with Class 1 up to 10 Meters
Cable	RS232 and USB 1.1 Y-cable
Cradle	RS232 port for point-to-point communication Modem interface to telephone line

### Physical and Environmental


Drop Test	1.2 Meter to concrete floor
Dimensions	123mm x 55mm x 25mm
Weight	150g
Temperature	Operation: 0°C ~ 50°C Storage: -20°C ~ 70°C
IP Rating	42
Humidity	20%~85% RH, non-condensing
Regulatory	CE, FCC, BSMI, VCCI

### Software Programming Tools

Unitech HT580 EasyJob  
MultiEJ Communication Utility

### Optional Models

HT580 Batch  
HT580 BT (Bluetooth)



### Unitech America

Los Angeles, Houston, Guadalajara  
<http://www.ute.com> e-mail: [inquiry@ute.com](mailto:inquiry@ute.com)  
<http://latin.unitech-adc.com> e-mail: [info@latin.unitech-adc.com](mailto:info@latin.unitech-adc.com)

### Unitech APAC

Taipei  
<http://www.unitech-adc.com> e-mail: [aidcsales@adc.unitech.com.tw](mailto:aidcsales@adc.unitech.com.tw)

### Unitech Japan

Tokyo  
<http://www.unitech-japan.co.jp> e-mail: [sales@unitech-japan.co.jp](mailto:sales@unitech-japan.co.jp)

### Unitech Europe

Tilburg / NL  
<http://www.unitech-europe.com> e-mail: [sales@unitech-europe.com](mailto:sales@unitech-europe.com)

### Unitech Greater China

Beijing, Suzhou, Shanghai, NingPo, Guang Zhou, Xiamen  
<http://www.ute.com.cn> <http://www.ute.cn> e-mail: [unitech@ute.com.cn](mailto:unitech@ute.com.cn)  
 Taipei <http://adc-utt.unitech.com.tw> e-mail: [barcode@unitech.com.tw](mailto:barcode@unitech.com.tw)

### Head Office

Taipei  
<http://www.unitech-adc.com> e-mail: [marketing@adc.unitech.com.tw](mailto:marketing@adc.unitech.com.tw)